

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
3 February 2005 (03.02.2005)

PCT

(10) International Publication Number
WO 2005/010317 A1

(51) International Patent Classification⁷:
10/60, 21/00

E21B 4/14,

(74) Common Representative: **LORGER, Tony**; 44 Dongarven Drive, Eagleby, Queensland 4207 (AU).

(21) International Application Number:

PCT/AU2004/000998

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(22) International Filing Date: 26 July 2004 (26.07.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2003903831

24 July 2003 (24.07.2003) AU

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant (*for all designated States except US*): **SPARR DRILLING EQUIPMENT PTY LTD** [AU/AU]; 44 Dongarven Drive, Eagleby, Queensland 4207 (AU).

(72) Inventors; and


(75) Inventors/Applicants (*for US only*): **LORGER, Tony** [AU/AU]; 44 Dongarven Drive, Eagleby, Queensland 4207 (AU). **RAVICHANDRA, Sugavanum** [IN/IN]; Bangalore (IN). **LORGER, Daniel, Paul** [AU/AU]; 144 Balgal Beach Road, Rollingstone, Queensland 4816 (AU).

Published:

- with international search report
- with amended claims

[Continued on next page]

(54) Title: DOWNHOLE HAMMER DRILL



(57) Abstract: There is provided a down hole hammer having a drive sub or chuck (10) having splines (11), and a drill bit (13) having a bit shank (14) having longitudinal splines (23) extending toward a bit head (15) having a bit face (16) bounded by a series of gauge row mounting portions (17), each of which has a carbide button insert (20). The bit shank splines (23) cooperate with chuck splines (11) to rotate the bit (13), the respective splines (23), (11) being proportioned to allow hammer motor exhaust air to pass down the splines. Drillings (37) are drilled from the termination of the spline milling, through to intersect with fluid passage (33) extending from sample recovery bore (22) to the bit face (16). A bore seal (32) is formed by milling a plurality of circumferential grooves (36), fed by a plurality of transverse holes (35) intersecting the air passage (33). Fluid passage (33) may be altered to fine tune the airflow to suit specific ground conditions, by effecting a change in diameter at point (38). The chuck (10) is provided with bleed ports (40) which direct air up the borehole when the bit is in its extended position to reduce contamination at the bit face.

WO 2005/010317 A1

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.